

Recommended P.C.B Layout(Top Side)

NOTES:

Current Rating: 0.5A AC,DC

Temperature Range: -20°C~+60°C


Contact Resistance: 40m max Ω

Insulation Resistance: 1000M min Ω


Withstanding Voltage: 500V

AC/minute

Material: LCP UL 94V-0



CIRCUIT



PIN NO.	PIN ASSIGNMENT
1#	DAT2
2#	CD/DAT3
3#	CMD
4#	VDD
5#	CLK
6#	VSS
7#	DAT0
8#	DAT1
9#	WP
10#	CD

6			
5			
4	SHELL	SWP	
3	SHELL	STEEL	NICKEL PLATED
2	CONTACT	COPPER ALLOY	GF PLATED AT CONTACT AREA, TN PLATED AT SOLDER PIN AREA NICKEL UNDERPLATED OVERALL
1	HOUSING	HI-TEMP PLASTIC	BLACK UL94V-0
NO.	PART NAME	MATERIAL	DESCRIPTION



东莞市旭明电子有限公司

					0	? .25
					0.0	? .20
0	15/11/08	NEW	Chi	Captain	0.00	? .15
REV	DATE	DESCRIPTION	NAME	APPRO.	GENERAL TOLERANCE UNLESS OTHERWISE NOTED	

DESIGN	
CHECK	
APPRO.	

TITLE:	TF卡座 贴板 H1.75 L12.05 翘边 黑胶芯LCP 铜壳镀镍			
PART NO.	TFB0003-000	CUSTOMER NO(REV)	1G	UNIT:mm
FILE NAME	151108-10	SHEET: 1 of 1	SCALE: 1:1	A4