



备注:

1.材质:

1.1胶芯: LCP+30%G.F UL94V-0

1.2端子: C5191, T=0.15mm;

1.3外壳: 不锈钢, T=0.15mm;

1.4卡钩: 不锈钢, T=0.35mm;

1.5弹片: 不锈钢, T=0.10mm

2.主要特性:

2.1额定电流: 5A FOR VBUS PIN;

1.25A FOR VCONN&GND PIN

0.25A FOR ALL OTHER PIN

2.2接触阻抗: N I I AL 40mΩ MAX, AFTER 50mΩ Max.

2.3绝缘阻抗: 100MΩ MIN 100V DC

2.4耐压测试: 100V AC

2.5沾锡性: 温度250? °C

2.6整体插入力: 5~20N

整体拔出力: 8~20N

2.7使用寿命: 10000次

2.8工作温度: -30°C~+80°C

5	弹片	不锈钢 T=0.10	——
4	卡钩	不锈钢 T=0.35	——
3	外壳	不锈钢 T=0.15	Ni PLATED
2	端子	C5191 T=0.15	Au PLATED 2U"
1	胶芯	LCP	UL 94V-0
NO.	PART NAME	MATERIAL	DESCRIPTION

**HE** 东莞市旭明电子有限公司

TITLE: USB C/M 拉伸式 外壳镀镍 夹板0.8 直端

PART NO.	UCU0090-000	CUSTOMER NO(REV)	1G	UNIT:mm
FILE NAME	180621-01	SHEET: 1 of 1	SCALE: 1:1	A4

					0	? .25			
					0.0	? .20		DESIGN	
0	18/06/21	NEW	Wyl	Dave	0.00	? .15		CHECK	
REV	DATE	DESCRIPTION	NAME	APPRO.	GENERAL TOLERANCE UNLESS OTHERWISE NOTED			APPRO.	