



RECOMMENDED PCB LAYOUT (COMPONENT SIDE)  
PCB LAYOUT TOLERANCE :±0.05(PCB T=1.2mm)

规格:  
接触阻抗:30milliohms MAX  
耐电压:500V AC  
绝缘阻抗:1000 MEGAohms MIN  
寿命:5000次, 插拔速度300次/小时  
插拔力: 插入力MAX:4.5Kgf Max.  
          拔出力MIN:0.45Kgf Min.  
工作温度:-30°C~+85°C  
盐雾测试: 24H

- DBC0020-XXX
- 000: 灰PA66铁壳镀金锁4.8螺丝
  - 001: 灰PA66铁壳镀镍锁4.8螺丝
  - 002: 蓝PA66铁壳镀金锁4.8螺丝
  - 003: 蓝PA66铁壳镀镍锁4.8螺丝
  - 004: 黑LCP铁壳镀金锁4.8螺丝
  - 005: 黑LCP铁壳镀镍锁4.8螺丝
- 产品流水号  
— 母座反向沉板  
— VGA 系列

5	FORK	BRASS	Matte Tin Plated
4	RIVET	BRASS	Ni Plated
3	SHELL	SPCC	Ni Plated
2	TERMINAL	C2680	Au/Matte Sn Plated
1	HOUSE	PA66	BLUE
UL 94V-0			
NO.	PART NAME	DESCRIPTION	REMARK

<b>HE</b> 东莞市旭明电子有限公司			
TITLE:	SLIM VGA 15P F 反向沉板 CL-0.8		
PART NO.	DBC0020-XXX	CUSTOMER NO(REV)	UNIT:mm
FILE NAME	090412-03	SHEET: 1 of 1	SCALE: 1:1 A4

				0	±0.25	DESIGN		
A	16'/08/19	更新图面及料号	Chi	Captain	0.0		±0.20	
							CHECK	
0	09'/04/12	NEW	Captain	Captain	0.00	±0.15		
REV	DATE	DESCRIPTION	NAME	APPRO.	GENERAL TOLERANCE UNLESS OTHERWISE NOTED		APPRO.	