



SPECIFICATION

- Electrical characteristics
 - Contact Current Rating:0.5 A
 - Dielectric Withstanding Voltage:300V AC
 - Insulation Resistance:a.Mate 100MΩ MIN at 500V/DC
 - b.Unmate 10MΩ MIN at 150V/DC
 - Contact Resistance:30mΩ MAX
 - Temperature Range:-20° C to +85° C
- Mechanical
 - Mating Face:44. IN MAX
 - Unmating Face:9.8N MIN;39.2N MAX
 - Durability:5000 Cycles
- material:
 - HOUSING:THERMOPLASTICS HIGH TEMP LCP+GLASS
 - FIBER WHITE COLOR,UL94V-0
 - CONTACT:Copper Alloy ,T=0.20MM
 - SHELL:Copper Alloy (SK7) ,T=0.40MM
- PLATING:
 - CONTACT:1~30u" GOLD/TIN PLATING ON CONTACT AREA
 - 100u"MIN, TIN PLATING ON SOLDER TAILS
 - 50u"MIN, NICKEL UNDERPLATING OVER ALL
 - SHELL:50u", NICKEL UNDERPLATING OVER ALL
- *Key control size

3	SHELL	SK7	NI:50u" MIN (可焊镍)
2	Molding件	CONTACT	C2680
1		Housing	LCP
			NI:30u"MIN AU:G/F Tin:100u"
			LCP 黑色 UL94-V0
NO.	PART NAME	MATERIAL	DESCRIPTION

HE 东莞市旭明电子有限公司

TITLE:	HDMI 19P 反向沉板2.00mm		
PART NO.	HAC0005-000	CUSTOMER NO(REV)	UNIT:mm
FILE NAME	20190625-00	SHEET: 1 of 1	SCALE: 1:1

				0	±0.25	DESIGN		
				0.0	±0.20			
A	2019.06.25	新版发行	LZX	LZX	0.00	±0.15	CHECK	
REV	DATE	DESCRIPTION	NAME	APPRO.	GENERAL TOLERANCE UNLESS OTHERWISE NOTED		APPRO.	