



NOTE:

1. MATERIAL:
 - 1.1 INSULATOR: LCP+30%GF, UL94V-0,
 - 1.2 CONTACT 1~4PIN: C5191R/H,
 - 1.3 CONTACT 5~9PIN: C5191R/H,
 - 1.4 SHELL: BRASS C2680R/H
2. PLATING:
 - 2.1 CONTACT: SELECTIVE GOLD PLATED ON CONTACT AREA
100u" Min. MATTE TIN PLATED ON SOLDER TAIL
50u" Min. NICKEL UNDER-PLATED
 - 2.2 SHELL: 50u" Min. NICKEL PLATED OVERALL
3. CHARACTERISTICS:
 - 3.1 ELECTRICAL CHARACTERISTICS;
CONTACT RESISTANCE: 30mΩ MAXIMUM
CONTACT CURRENT RATING: 1.5A
DIELECTRIC WITHSTANDING VOLTAGE: 500 V R.M.S.
INSULATION RESISTANCE 1000 MEGOHMS MIN
OPERATING TEMPERATURE: -25°C ~ +85°C
 - 3.2 MECHANICAL:
MATING FORCE: 3.57Kg.Max.
UNMATING FORCE: 1.02Kg.Min.
4. DESIGN STANDARD ACCORDING TO USB_3.0 SPECIFICATION.

HE 东莞市旭明电子有限公司

					0	±0.25			
					0.0	±0.20	DESIGN		
A	19'/04/12	NEW	Dave	Captain	0.00	±0.15	CHECK		
REV	DATE	DESCRIPTION	NAME	APPRO.	GENERAL TOLERANCE UNLESS OTHERWISE NOTED		APPRO.		

TITLE:	USB 3.0 AF H3.5 SMT 无翻 边贴切脚外移			
PART NO.	UAA0007-005	CUSTOMER NO(REV)	1G	UNIT:mm
FILE NAME	190412-01	SHEET: 1 of 1	SCALE: 1:1	A4