



USB-AM SOLDER TAIL(焊线式)

特性: Specifications

电器 Electrical:

接触阻抗: Contact Resistance
30milliohms MAX

耐电压: Dielectric Withstanding Voltage
50V AC AT sea Lev0L

绝缘阻抗: Insulation Resistance:
100MEGA ohms MIN

材料: Material:

塑胶: Housing: Thermoplastics, PBT料蓝色塑胶

端子: Contact: Copper Alloy 铜合金

铁壳: Shell: SPCC-SD 铁材

电镀: Finish:

端子: Contact: Plated Gold in Contact Area;
Tin On Solder Tails

接触点镀金, 脚镀锡

铁壳: Shell:

Nicket Plating All Over 镀镍

5			
4			
3	外壳	SPCC	Ni Plating
2	端子	Copper Alloy	SN/AU Plating
1	塑胶	PBT	Blue compound
NO.	PART NAME	DESCRIPTION	REMARK

HE 东莞市旭明电子有限公司

TITLE:	USB 3.0 A TYPE 夹板1.0MM		
PART NO.	UAU0001-000	CUSTOMER NO(REV)	1G UNIT: mm
FILE NAME	191108-01	SHEET: 1 of 1	SCALE: 1:1 A4

				0	±0.25	DESIGN			
				0.0	±0.20				
A	19'11/08	更新图面	HQ	Stn	0.00	±0.15	CHECK		
REV	DATE	DESCRIPTION	NAME	APPRO.	GENERAL TOLERANCE UNLESS OTHERWISE NOTED		APPRO.		