



UAA0007-XXX
 004: 黑LCP
 005: 蓝LCP

- NOTE:
- MATERIAL:
 - INSULATOR: LCP+30%GF, UL94V-0,
 - CONTACT 1~4PIN: C5191R/H,
 - CONTACT 5~9PIN: C5191R/H,
 - SHELL: BRASS C2680R/H
 - PLATING:
 - CONTACT: SELECTIVE GOLD PLATED ON CONTACT AREA 100u" Min. MATTE TIN PLATED ON SOLDER TAIL 50u" Min. NICKEL UNDER-PLATED
 - SHELL: 50u" Min. NICKEL PLATED OVERALL
 - CHARACTERISTICS:
 - ELECTRICAL CHARACTERISTICS;
 - CONTACT RESISTANCE: 30mΩ MAXIMUM
 - CONTACT CURRENT RATING: 1.5A
 - DIELECTRIC WITHSTANDING VOLTAGE: 500 V R.M.S.
 - INSULATION RESISTANCE 1000 MEGOHMS MIN
 - OPERATING TEMPERATURE: -25°C ~ +85°C
 - MECHANICAL:
 - MATING FORCE: 3.57Kg.Max.
 - UNMATING FORCE: 1.02Kg.Min.
 - DESIGN STANDARD ACCORDING TO USB_3.0 SPECIFICATION.

6			
5			
4			
3	外壳	BRASS	NICKEL PLATED
2	端子	BRONZE	GOLD/TIN PLATED
1	胶芯	LCP	UL94V-0
NO.	PART NAME	MATERIAL	DESCRIPTION

HE 东莞市旭明电子有限公司

TITLE: USB3.0 AF 沉板 SMT H=3.5 铁壳脚前贴后插(方脚)

PART NO.	UAA0007-XXX	CUSTOMER NO(REV)	1G	UNIT:mm
FILE NAME	181226-01	SHEET: 1 of 1	SCALE: 1:1	A4

REV	DATE	DESCRIPTION	NAME	APPRO.	GENERAL TOLERANCE UNLESS OTHERWISE NOTED	APPRO.
0	18'/12/26	NEW	Chi	Captain	0 ±0.25 0.0 ±0.20 0.00 ±0.15	DESIGN CHECK