



SPECIFICATIONS

1. OPERATING CURRENT: 0.5A MAX.
2. OPERATION TEMPERATURE: -25°C TO $+85^{\circ}\text{C}$
3. DIELECTRIC WITHSTANDING VOLTAGE:
 - 500Volts AC BETWEEN ADJACENT TERMINAL (UNMATE)
 - 300Volts AC BETWEEN ADJACENT TERMINAL (MATE)
4. INSULATION RESISTANCE:
 - 100Mohm MIN. (UNMATED); 10Mohm MIN. (MATED)
5. HDMI SPECIFICATION COMPLIANCE

5			
4			
3	CONTACTS	COPPER ALLOY	Au/Tin PLATED
2	HOUSING	LCP BLACK	UL94V-0
1	SHELL	COPPER ALLOY OR SPCC	Au/Ni PLATED
NO.	PART NAME	DESCRIPTION	REMARK

HE 东莞市旭明电子有限公司

TITLE: HDMI A/F 板上SMT H=6.17

PART NO.	HAB0003-000	CUSTOMER NO (REV)	1G	UNIT:mm
FILE NAME	140618-10	SHEET: 1 of 1	SCALE: 1:1	A4

				0	± 0.25	DESIGN		
				0.0	± 0.20	CHECK		
0	14/06/18	NEW	Chi	Captain	0.00	± 0.15	APPRO.	
REV	DATE	DESCRIPTION	NAME	APPRO.	GENERAL TOLERANCE UNLESS OTHERWISE NOTED		APPRO.	